

# Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 28, 2018

Revision: June 28, 2018

## 1 Identification

- **Product identifier**
- **Trade name:** **G-S Hypo Cement**
- **Other means of identification:** No other identifiers
- **Recommended use and restriction on use**
- **Recommended use:** Adhesives
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**  
G-S Supplies Inc.  
1150 University Avenue, Suite 5  
Rochester, NY 14607 USA  
Tel (585) 241-2370
- **Emergency telephone number:**  
ChemTel Inc.  
(800)255-3924 (North America)  
+1 (813)248-0585 (International)

## 2 Hazard(s) identification

- **Classification of the substance or mixture**

Flam. Liq. 2	H225	Highly flammable liquid and vapor.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2A	H319	Causes serious eye irritation.
Carc. 2	H351	Suspected of causing cancer.
STOT SE 3	H335-H336	May cause respiratory irritation. May cause drowsiness or dizziness.
STOT RE 2	H373	May cause damage to the hearing organs through prolonged or repeated exposure.

- **Label elements**

- **GHS label elements**

This product is a consumer product and is labeled in accordance with the US Consumer Product Safety Commission. GHS labeling is not required per 29CFR1910.1200(b)(5)(v). The labeling below applies to industrial/professional products.

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms:**



GHS02 GHS07 GHS08

- **Signal word:** Danger

- **Hazard statements:**

H225 Highly flammable liquid and vapor.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H351 Suspected of causing cancer.  
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

(Cont'd. on page 2)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 28, 2018

Revision: June 28, 2018

**Trade name: G-S Hypo Cement**

(Cont'd. of page 1)

- H373 May cause damage to the hearing organs through prolonged or repeated exposure.
- Precautionary statements:**
- P201 Obtain special instructions before use.
  - P202 Do not handle until all safety precautions have been read and understood.
  - P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
  - P233 Keep container tightly closed.
  - P243 Take precautionary measures against static discharge.
  - P260 Do not breathe mist/vapors/spray.
  - P264 Wash thoroughly after handling.
  - P271 Use only outdoors or in a well-ventilated area.
  - P280 Wear protective gloves and eye protection.
  - P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
  - P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
  - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
  - P308+P313 IF exposed or concerned: Get medical advice/attention.
  - P332+P313 If skin irritation occurs: Get medical advice/attention.
  - P362+P364 Take off contaminated clothing and wash it before reuse.
  - P337+P313 If eye irritation persists: Get medical advice/attention.
  - P370+P378 In case of fire: Use foam, powder, or carbon dioxide for extinction.
  - P403+P235 Store in a well-ventilated place. Keep cool.
  - P405 Store locked up.
  - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Other hazards** There are no other hazards not otherwise classified that have been identified.

### 3 Composition/information on ingredients

**Chemical characterization: Mixtures**

**Components:**

142-82-5	heptane ⚠ Flam. Liq. 2, H225 ⚠ Asp. Tox. 1, H304 ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	20-40%
108-38-3	m-xylene ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	10-20%
106-42-3	p-xylene ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	5-10%
100-41-4	ethylbenzene ⚠ Flam. Liq. 2, H225 ⚠ Carc. 2, H351; STOT RE 2, H373; Asp. Tox. 1, H304	5-10%

(Cont'd. on page 3)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 28, 2018

Revision: June 28, 2018

**Trade name: G-S Hypo Cement**

(Cont'd. of page 2)

	<ul style="list-style-type: none"> <li>⚠ Acute Tox. 4, H332</li> </ul>	
95-47-6	<ul style="list-style-type: none"> <li>o-xylene</li> <li>⚠ Flam. Liq. 3, H226</li> <li>⚠ Asp. Tox. 1, H304</li> <li>⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335</li> </ul>	1-5%

· **Additional information:**

For the wording of the listed Hazard Statements, refer to section 16.

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret.

### 4 First-aid measures

· **Description of first aid measures**

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

· **After skin contact:**

Do not pull solidified product away from the skin.  
Clean with water and soap.  
If skin irritation continues, consult a doctor.

· **After eye contact:**

Protect unharmed eye.  
Remove contact lenses if worn, if possible.  
Rinse opened eye for several minutes under running water. Then consult a doctor.

· **After swallowing:**

Rinse out mouth and then drink plenty of water.  
Do not induce vomiting; immediately call for medical help.

· **Most important symptoms and effects, both acute and delayed:**

Headache  
Coughing  
Dizziness  
Breathing difficulty  
Disorientation

· **Danger:**

Danger of impaired breathing.  
Danger of cerebral edema.  
Danger of convulsion.

· **Indication of any immediate medical attention and special treatment needed:**

If swallowed, gastric irrigation with added, activated carbon.  
Monitor circulation, possible shock treatment.  
If necessary oxygen respiration treatment.  
Medical supervision for at least 48 hours.  
Later observation for pneumonia and pulmonary edema.

### 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

(Cont'd. on page 4)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 28, 2018

Revision: June 28, 2018

**Trade name: G-S Hypo Cement**

(Cont'd. of page 3)

Water fog / haze

Foam

Fire-extinguishing powder

Carbon dioxide

Sand

- **For safety reasons unsuitable extinguishing agents:** Water stream.
- **Special hazards arising from the substance or mixture**  
In case of fire, the following can be released:  
Carbon monoxide (CO)  
In certain fire conditions, traces of other toxic gases cannot be excluded.
- **Advice for firefighters**
- **Protective equipment:**  
Wear self-contained respiratory protective device.  
Wear fully protective suit.
- **Additional information:** Cool endangered containers with water fog.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Use respiratory protective device against the effects of fumes/dust/aerosol.  
Wear protective equipment. Keep unprotected persons away.  
Ensure adequate ventilation.  
Keep away from ignition sources.  
Protect from heat.
- **Environmental precautions**  
Do not allow to enter sewers/ surface or ground water.  
Inform respective authorities in case of seepage into water course or sewage system.
- **Methods and material for containment and cleaning up**  
Allow to solidify. Pick up mechanically.  
Send for recovery or disposal in suitable receptacles.  
Clean the affected area carefully; suitable cleaners are:  
Organic solvent
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

### 7 Handling and storage

- **Handling**
- **Precautions for safe handling:**  
Open and handle receptacle with care.  
Keep out of reach of children.  
Avoid contact with the eyes and skin.  
Use only in well ventilated areas.  
Keep receptacles tightly sealed.  
Keep away from heat and direct sunlight.
- **Information about protection against explosions and fires:**

(Cont'd. on page 5)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 28, 2018

Revision: June 28, 2018

**Trade name: G-S Hypo Cement**

(Cont'd. of page 4)

Keep ignition sources away - Do not smoke.  
 Protect against electrostatic charges.  
 Emergency cooling must be available in case of nearby fire.

- **Conditions for safe storage, including any incompatibilities**
- **Requirements to be met by storerooms and receptacles:**  
 Avoid storage near extreme heat, ignition sources or open flame.  
 Store in cool, dry conditions in well sealed receptacles.
- **Information about storage in one common storage facility:**  
 Store away from foodstuffs.  
 Store away from oxidizing agents.
- **Specific end use(s)** No relevant information available.

### 8 Exposure controls/personal protection

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**142-82-5 heptane**

PEL (USA)	Long-term value: 2000 mg/m <sup>3</sup> , 500 ppm
REL (USA)	Long-term value: 350 mg/m <sup>3</sup> , 85 ppm Ceiling limit value: 1800* mg/m <sup>3</sup> , 440* ppm *15-min
TLV (USA)	Short-term value: 2050 mg/m <sup>3</sup> , 500 ppm Long-term value: 1640 mg/m <sup>3</sup> , 400 ppm
EL (Canada)	Short-term value: 500 ppm Long-term value: 400 ppm
EV (Canada)	Short-term value: 2045 mg/m <sup>3</sup> , 500 ppm Long-term value: 1635 mg/m <sup>3</sup> , 400 ppm
LMPE (Mexico)	Short-term value: 500 ppm Long-term value: 400 ppm

**108-38-3 m-xylene**

PEL (USA)	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL (USA)	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV (USA)	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI
EL (Canada)	Short-term value: 150 ppm Long-term value: 100 ppm
LMPE (Mexico)	Short-term value: 150 ppm Long-term value: 100 ppm A4, IBE

**106-42-3 p-xylene**

PEL (USA)	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL (USA)	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm

(Cont'd. on page 6)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 28, 2018

Revision: June 28, 2018

**Trade name: G-S Hypo Cement**

(Cont'd. of page 5)

TLV (USA)	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI
EL (Canada)	Short-term value: 150 ppm Long-term value: 100 ppm
LMPE (Mexico)	Short-term value: 150 ppm Long-term value: 100 ppm A4, IBE

**100-41-4 ethylbenzene**

PEL (USA)	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL (USA)	Short-term value: 545 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV (USA)	Long-term value: 87 mg/m <sup>3</sup> , 20 ppm BEI
EL (Canada)	Long-term value: 20 ppm IARC 2B
EV (Canada)	Short-term value: 540 mg/m <sup>3</sup> , 125 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
LMPE (Mexico)	Long-term value: 20 ppm

**95-47-6 o-xylene**

PEL (USA)	Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
REL (USA)	Short-term value: 655 mg/m <sup>3</sup> , 150 ppm Long-term value: 435 mg/m <sup>3</sup> , 100 ppm
TLV (USA)	Short-term value: 651 mg/m <sup>3</sup> , 150 ppm Long-term value: 434 mg/m <sup>3</sup> , 100 ppm BEI
EL (Canada)	Short-term value: 150 ppm Long-term value: 100 ppm
LMPE (Mexico)	Short-term value: 150 ppm Long-term value: 100 ppm A4, IBE

**Ingredients with biological limit values:**

**108-38-3 m-xylene**

BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

**106-42-3 p-xylene**

BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

**100-41-4 ethylbenzene**

BEI (USA)	0.7 g/g creatinine Medium: urine
-----------	-------------------------------------

(Cont'd. on page 7)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 28, 2018

Revision: June 28, 2018

**Trade name: G-S Hypo Cement**

(Cont'd. of page 6)

	Time: end of shift at end of workweek Parameter: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	
	Medium: end-exhaled air Time: not critical Parameter: Ethyl benzene (semi-quantitative)

**95-47-6 o-xylene**

BEI (USA)	1.5 g/g creatinine Medium: urine Time: end of shift Parameter: Methylhippuric acids
-----------	--

- **Exposure controls**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing.  
Wash hands before breaks and at the end of work.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.
- **Engineering controls:** Provide adequate ventilation.
- **Breathing equipment:**  
Not necessary if room is well-ventilated.  
Use suitable respiratory protective device in case of insufficient ventilation.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

- **For the permanent contact gloves made of the following materials are suitable:**  
Nitrile rubber, NBR  
Butyl rubber, BR
- **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**  
Natural rubber, NR
- **Not suitable are gloves made of the following materials:** PVA gloves
- **Eye protection:**



Safety glasses

- **Body protection:** Protective work clothing
- **Limitation and supervision of exposure into the environment**  
No relevant information available.
- **Risk management measures** No relevant information available.

### 9 Physical and chemical properties

(Cont'd. on page 8)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 28, 2018

Revision: June 28, 2018

**Trade name: G-S Hypo Cement**

(Cont'd. of page 7)

**Information on basic physical and chemical properties**
**Appearance:**

<b>Form:</b>	Liquid
<b>Color:</b>	Transparent
<b>Odor:</b>	Aromatic
<b>Odor threshold:</b>	Not determined.

<b>pH-value:</b>	Not determined.
<b>Melting point/Melting range:</b>	Not determined.
<b>Boiling point/Boiling range:</b>	98 °C (208.4 °F)

<b>Flash point:</b>	11 °C (51.8 °F)
---------------------	-----------------

<b>Flammability (solid, gaseous):</b>	Not applicable.
---------------------------------------	-----------------

<b>Auto-ignition temperature:</b>	215 °C (419 °F)
-----------------------------------	-----------------

<b>Decomposition temperature:</b>	Not determined.
-----------------------------------	-----------------

<b>Danger of explosion:</b>	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
-----------------------------	--

**Explosion limits**

<b>Lower:</b>	1.1 Vol %
<b>Upper:</b>	6.7 Vol %

<b>Oxidizing properties:</b>	Non-oxidizing.
------------------------------	----------------

<b>Vapor pressure at 20 °C (68 °F):</b>	48 hPa (36 mm Hg)
---	-------------------

**Density:**

<b>Relative density:</b>	1.01
<b>Vapor density:</b>	Not determined.
<b>Evaporation rate:</b>	Not determined.

**Solubility in / Miscibility with**

<b>Water:</b>	Not miscible or difficult to mix.
---------------	-----------------------------------

<b>Partition coefficient (n-octanol/water):</b>	Not determined.
---	-----------------

**Viscosity**

<b>Dynamic:</b>	Not determined.
<b>Kinematic at 40 °C (104 °F):</b>	>21 mm <sup>2</sup> /sec

<b>Other information</b>	No relevant information available.
--------------------------	------------------------------------

### 10 Stability and reactivity

· **Reactivity:** No relevant information available.

· **Chemical stability:**

· **Thermal decomposition / conditions to be avoided:**

No decomposition if used and stored according to specifications.

· **Possibility of hazardous reactions**

Reacts with strong acids.

Highly flammable liquid and vapor.

(Cont'd. on page 9)



## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 28, 2018

Revision: June 28, 2018

**Trade name: G-S Hypo Cement**

(Cont'd. of page 8)

- Forms flammable gases / fumes.
- Reacts with oxidizing agents.
- Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.
- Reacts with peroxides and other radical forming substances.
- **Conditions to avoid** Excessive heat.
- **Incompatible materials** Oxidizers
- **Hazardous decomposition products**  
Carbon monoxide and carbon dioxide  
Hydrocarbons

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

**100-41-4 ethylbenzene**

Oral	LD50	3500 mg/kg (rat)
------	------	------------------

- **Primary irritant effect:**
- **On the skin:** Irritant to skin and mucous membranes.
- **On the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.

· **IARC (International Agency for Research on Cancer):**

100-41-4	ethylbenzene		2B
----------	--------------	--	----

· **NTP (National Toxicology Program):**

None of the ingredients are listed.

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

· **Probable route(s) of exposure:**

- Ingestion.
- Inhalation.
- Eye contact.
- Skin contact.

- **Carcinogenicity:** Suspected of causing cancer.
- **Reproductive toxicity:** Based on available data, the classification criteria are not met.
- **STOT-single exposure:**  
May cause respiratory irritation.  
May cause drowsiness or dizziness.
- **STOT-repeated exposure:**  
May cause damage to the hearing organs through prolonged or repeated exposure.
- **Aspiration hazard:** Based on available data, the classification criteria are not met.

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity** Toxic to aquatic life with long lasting effects.

(Cont'd. on page 10)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 28, 2018

Revision: June 28, 2018

**Trade name: G-S Hypo Cement**


(Cont'd. of page 9)

- **Persistence and degradability** The product is partially biodegradable. Significant residuals remain.
- **Bioaccumulative potential:**  
Due to the distribution coefficient n-octanol/water an accumulation in organisms is not expected.
- **Mobility in soil:** No relevant information available.
- **Ecotoxic effects:**
- **Remark:** Very toxic for fish
- **Additional ecological information**
- **General notes:** Do not allow product to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Can be disposed of with household garbage after solidification following consultation with the waste disposal facility operator and the pertinent authorities and adhering to the necessary technical regulations. The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.
- **Uncleaned packagings**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Solvent naphtha

### 14 Transport information

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>· <b>UN-Number</b></li> <li>· <b>DOT, IATA</b></li> <li>· <b>ADR, IMDG</b></li> </ul>               | <p>UN1133 or ID8000<br/>UN1133</p>                   |
| <ul style="list-style-type: none"> <li>· <b>UN proper shipping name</b></li> <li>· <b>DOT, IATA</b></li> <li>· <b>ADR, IMDG</b></li> </ul> | <p>Adhesives or Consumer Commodity<br/>ADHESIVES</p> |
| <ul style="list-style-type: none"> <li>· <b>Transport hazard class(es)</b></li> <li>· <b>DOT</b></li> </ul>                                |  |
|   |  |
| <ul style="list-style-type: none"> <li>· <b>Class</b></li> <li>· <b>Label</b></li> </ul>   | <p>3 or 9<br/>3 or 9</p>                             |

(Cont'd. on page 11)

**Safety Data Sheet**

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 28, 2018

Revision: June 28, 2018

**Trade name: G-S Hypo Cement**

(Cont'd. of page 10)

· **ADR**



· **Class** 3 (F1)  
 · **Label** 3

· **IMDG**



· **Class** 3  
 · **Label** 3

· **IATA**



· **Class** 3 or 9  
 · **Label** 3 or 9

· **Packing group**

· **DOT, IATA** II or not applicable  
 · **ADR, IMDG** II

· **Environmental hazards**

Product contains environmentally hazardous substances: heptane

· **Marine pollutant:**



Yes

· **Special precautions for user**

Not applicable.

· **Danger code (Kemler):**

33

· **EMS Number:**

F-E,S-D

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**

Not applicable.

· **Transport/Additional information:**



Excepted Quantities (EQ)

EQ Code: E2

Maximum net quantity per inner packaging: 30 mL

Maximum net quantity per outer packaging: 500 mL

· **DOT**

(Cont'd. on page 12)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 28, 2018

Revision: June 28, 2018

**Trade name: G-S Hypo Cement**

(Cont'd. of page 11)



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

Labeling as a Marine Pollutant is only required for bulk single package shipments. Bulk packaging consists of a maximum capacity of greater than 450 L (119 gallons) for a liquid and a maximum net mass greater than 400 kg (882 pounds) for a solid. (See 171.4(c))

· **ADR**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 5.2.1.8.1)

· **IMDG**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 5 L each.

Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to provisions relevant to marine pollutants. (See 2.10.2.7)

· **IATA**



Limited Quantity for packages less than 30 kg gross and inner packagings less than 0.5 L each / 1 L net.

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

108-38-3	m-xylene
106-42-3	p-xylene
100-41-4	ethylbenzene

(Cont'd. on page 13)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 28, 2018

Revision: June 28, 2018

**Trade name: G-S Hypo Cement**

(Cont'd. of page 12)

95-47-6	o-xylene
---------	----------

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed.

· **Proposition 65 (California)**

· **Chemicals known to cause cancer:**

100-41-4	ethylbenzene
----------	--------------

· **Chemicals known to cause developmental toxicity for females:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity for males:**

None of the ingredients are listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

· **EPA (Environmental Protection Agency):**

142-82-5	heptane	D
108-38-3	m-xylene	I
106-42-3	p-xylene	I
100-41-4	ethylbenzene	D
95-47-6	o-xylene	I

· **IARC (International Agency for Research on Cancer):**

100-41-4	ethylbenzene	2B
----------	--------------	----

· **Canadian Domestic Substances List (DSL) (Substances not listed.):**

All ingredients are listed.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Abbreviations and acronyms:**

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bio-accumulable, Toxic
- vPvB: very Persistent and very Bioaccumulative
- OSHA: Occupational Safety & Health Administration
- Flam. Liq. 2: Flammable liquids – Category 2
- Flam. Liq. 3: Flammable liquids – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
- Carc. 2: Carcinogenicity – Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Asp. Tox. 1: Aspiration hazard – Category 1

(Cont'd. on page 14)

## Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Printing date: June 28, 2018

Revision: June 28, 2018

**Trade name: G-S Hypo Cement**

(Cont'd. of page 13)

· **Sources**

Website, European Chemicals Agency ([echa.europa.eu](http://echa.europa.eu))

Website, US EPA Substance Registry Services ([ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do](http://ofmpub.epa.gov/sorinternet/registry/substreg/home/overview/home.do))

Website, Chemical Abstracts Registry, American Chemical Society ([www.cas.org](http://www.cas.org))

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573

Website: [www.chemtelinc.com](http://www.chemtelinc.com)